

The XSClimber

Our electric-powered, self-reeving traction hoist. Every feature you will need in one compact, lightweight design.

Heavy duty.
Lightweight.
Compact.

| | |
|----------------------------|-----------------------|
| Working load limit: | 400 kg. & 500 kg. |
| Hoisting speed: | 12 m/min. (limited) |
| Self-weight: | 49.2 kg. |
| Dimensions: | 439 x 298 x 456 mm. |
| Materials: | Aluminium, composites |

Easy maintenance

- ✓ 4-point-access
- ✓ Central PCB: all electric components in 1 place
- ✓ IP54 Water and dust proof housing
- ✓ Ergonomic handles
- ✓ Bottom supports for easy access
- ✓ External oil level meter

Individual control panel

- ✓ Digital running hours counter
- ✓ Emergency stop button
- ✓ Lifting & lowering function
- ✓ Overload indicator
- ✓ Overheating indicator



SAFETY FEATURES

- Suspension point with pre-calibrated, integrated overload detection.
- Mechanical brake release lever for safe descent in case of emergency.
- Interchangeable, external secondary brake systems:



Slack Rope Device

- Designed, tested and certified in accordance with EN1808:1999+A1:2010



Overspeed Device

- Designed and tested to comply with ASME A120.1-2008